



BR PLUS

Thermoplastic rubber coated super reinforced non-woven polyester fabric hose with a spring steel wire helix



LENGTHS	SIZES	COLORS	TEMPATURE RANGE
25 AND 50 FEET	1.5" TO 16" *	BLACK (AVAILABLE IN BLUE)	50°F TO 285°F; INTERMITTENT TO 325°F

APPLICATIONS

- Suitable for more demanding positive and negative pressure applications.
- Designed for applications with wide temperature ranges.
- Great moisture and UV resistance.
- Excellent chemical resistance.
- Smooth interior assures minimal friction loss and efficient air flow.
- Available with factory-installed 2" soft cuffs.

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COM-PRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.22	.024	2.75	3:1	29	50
3	.33	.024	3	3:1	29	29
4	.5	.024	3.5	4:1	29	25
5	.63	.024	5	4:1	29	22
6	.7	.024	6	4:1	14	16
8	1	.024	7.5	4:1	8	12
10	1.25	.024	9	4:1	7	9
12	1.75	.024	10	4:1	4	8

* FURTHER DIAMETERS AND LENGTHS AVAILABLE ON REQUEST.



SCAN FOR PRODUCT INFORMATION

DISCLAIMER: THE DATA PROVIDED IS INTENDED AS A GUIDE ONLY AND SHOULD NOT BE INTERPRETED AS A WARRANTY. IT IS NOT INTENDED TO BE USED TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR ANY SPECIFIC CUSTOMER APPLICATION. SIFTEX STRONGLY SUGGESTS THAT EACH CUSTOMER THOROUGHLY TEST THE PROSPECTIVE PRODUCT IN THEIR OWN MANUFACTURING FACILITY TO DETERMINE THE ACTUAL SUITABILITY OF THE PRODUCT IN THEIR SPECIFIC APPLICATION.

