



# CP HD

Hi-Flex CP- HD hose: Very heavy-weight polyurethane hose reinforced with a coated spring steel wire helix.

LENGTHS	SIZES	COLORS	TEMPERATURE RANGE
25"	4" TO 18" (CUSTOM TO 24") *	CLEAR, BLACK, TRANSLUCENT BLUE	-65° TO 225° F -54° TO 107° C

## APPLICATIONS

- Great abrasion resistance and high tear strength
- Superior chemical resistance and excellent flexibility
- Designed for applications with wide temperature ranges
- Ideal for severe service applications
- Very good low temperature flexibility
- Clear is manufactured with FDA acceptable materials
- Wall Thickness = .060"
- Available with factory-installed 2" soft cuffs

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
4	1	4	2:1	29	34
5	1.3	5	2:1	17	33
6	1.5	6	2:1	15	32
8	1.9	8	2:1	9	29
10	2.2	10	2:1	4	25
12	2.6	12	2:1	2.5	20
14	3.8	14	2:1	3.5	18
16	4.2	16	2:1	2.5	15
18	4.8	18	2:1	1.5	12



\* FURTHER DIAMETERS AND LENGTHS AVAILABLE ON REQUEST.



SCAN FOR PRODUCT INFORMATION

**DISCLAIMER:** THE DATA PROVIDED IS INTENDED AS A GUIDE ONLY AND SHOULD NOT BE INTERPRETED AS A WARRANTY. IT IS NOT INTENDED TO BE USED TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR ANY SPECIFIC CUSTOMER APPLICATION. SIFTEX STRONGLY SUGGESTS THAT EACH CUSTOMER THOROUGHLY TEST THE PROSPECTIVE PRODUCT IN THEIR OWN MANUFACTURING FACILITY TO DETERMINE THE ACTUAL SUITABILITY OF THE PRODUCT IN THEIR SPECIFIC APPLICATION.

