



CP-SD

Hi-Flex CP-SD hose: Medium weight static dissipative polyurethane hose reinforced with a bronze coated spring steel wire helix.

LENGTHS	SIZES	COLORS	TEMPATURE RANGE
25', 50'	2" TO 12"	TRANSPARENT AND BLACK	-65° TO 225° F -54° TO 107° C

APPLICATIONS

- Great abrasion resistance and high tear strength
- Superior chemical resistance and excellent flexibility
- Designed for applications with wide temperature ranges
- Ideal for clean rooms and material handling applications
- Reduces static build-up in material handling
- Clear is manufactured with FDA acceptable materials
- Available with factory installed 2" soft cuffs
- Wall Thickness = .030"
- Surface Resistance level: 10⁹ - 10¹⁰

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.25	2	3:1	29	30
2.5	.32	2.5	3:1	29	30
3	.4	3	3:1	29	29
4	.7	4	3:1	29	25
5	.9	5	3:1	17	22
6	1	6	3:1	15	19
8	1.5	8	3:1	9	14
10	1.6	8	3:1	4	11
12	2	10	3:1	2.2	10



* FURTHER DIAMETERS AND LENGTHS AVAILABLE ON REQUEST.



SCAN FOR PRODUCT INFORMATION

DISCLAIMER: THE DATA PROVIDED IS INTENDED AS A GUIDE ONLY AND SHOULD NOT BE INTERPRETED AS A WARRANTY. IT IS NOT INTENDED TO BE USED TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR ANY SPECIFIC CUSTOMER APPLICATION. SIFTEX STRONGLY SUGGESTS THAT EACH CUSTOMER THOROUGHLY TEST THE PROSPECTIVE PRODUCT IN THEIR OWN MANUFACTURING FACILITY TO DETERMINE THE ACTUAL SUITABILITY OF THE PRODUCT IN THEIR SPECIFIC APPLICATION.

