



NEO/PE

Construction: Double-ply neoprene coated polyester fabric hose reinforced with a spring steel wire helix.



LENGTHS	SIZES	COLORS	TEMPERATURE RANGE
25'	1" TO 24" , CUSTOM TO 60" *	BLACK	-40° TO 250° F -40° TO 121° C

APPLICATIONS

- Listed as UL 94V-0 flame retardant

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL. BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1	.12	N/A	1.1	3:1	29	30
2	.25	N/A	2	4:1	29	30
3	.34	N/A	2.4	4:1	29	30
4	.56	N/A	3.1	5:1	29	30
5	.75	N/A	3.5	5:1	17	17
6	.95	N/A	4.5	5:1	21	11
7	.99	N/A	5	5:1	14	8
8	1.1	N/A	6	6:1	12	6.5
9	1.2	N/A	6.5	6:1	9	6
10	1.3	N/A	7.5	8:1	7	5
12	1.5	N/A	8	8:1	4	4.3
14	2.2	N/A	10	8:1	3.7	3.6
16	2.5	N/A	12	8:1	2.5	3.2
18	2.8	N/A	13	8:1	1.8	3
20	3.1	N/A	14	8:1	1.3	2.6
22	3.5	N/A	15	8:1	.81	2.4
24	3.8	N/A	17	8:1	.75	2.2

* FURTHER DIAMETERS AND LENGTHS AVAILABLE ON REQUEST.



SCAN FOR PRODUCT INFORMATION

DISCLAIMER: THE DATA PROVIDED IS INTENDED AS A GUIDE ONLY AND SHOULD NOT BE INTERPRETED AS A WARRANTY. IT IS NOT INTENDED TO BE USED TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR ANY SPECIFIC CUSTOMER APPLICATION. SIFTEX STRONGLY SUGGESTS THAT EACH CUSTOMER THOROUGHLY TEST THE PROSPECTIVE PRODUCT IN THEIR OWN MANUFACTURING FACILITY TO DETERMINE THE ACTUAL SUITABILITY OF THE PRODUCT IN THEIR SPECIFIC APPLICATION.

