



COMPARATIVE PROPERTIES CHART: SIFT-SOCK™ FABRICS

REVISED
JANUARY 2018

* DISCLAIMER: THE DATA PROVIDED IS INTENDED AS A GUIDE ONLY AND SHOULD NOT BE INTERPRETED AS A WARRANTY. SIFTEX RECOMMENDS EACH CUSTOMER THOROUGHLY TEST THE SIFT-SOCK FABRIC IN THEIR OWN MANUFACTURING FACILITY TO DETERMINE THE SUITABILITY OF THE FABRIC IN THEIR SPECIFIC APPLICATION.

	PTFE WOVEN LAMINATE FABRIC (WHITE)	#022 WOVEN PTFE FABRIC (WHITE)	RUBBER-COATED NYLON (RCN) (WHITE)	4019 CORDURA NYLON (WHITE)	NYLON SATIN FABRIC (WHITE)	#322 POLYESTER FABRIC (WHITE)	#180 POLYESTER MONOFILAMENT (WHITE)	THERMO-FLEX SILICONE/NYLON (LIGHT GRAY)	FEATHER-FLEX™ (WHITE)
ABRASION RESISTANCE TABER TEST METHOD	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
TEAR & FLEX FATIGUE RESISTANCE FLEX MODULUS, PSI	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
OIL & GREASE RESISTANCE	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
HARSH CHEMICAL RESISTANCE	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
MILD CHEMICAL RESISTANCE	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
SUITABLE FOR CIP	YES	NO (WILL LEAK)	YES	NO (WILL LEAK)	NO (WILL LEAK)	NO (WILL LEAK)	NO (WILL LEAK)	YES	YES
WATER RESISTANCE	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
UV LIGHT & OUTDOOR EXPOSURE RESISTANCE	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
TEMPERATURE RANGE CONTINUOUS	-390 TO 500°F -234 TO 260°C	-390 TO 500°F -234 TO 260°C	-350 TO 500°F -212 TO 260°C	-0 TO 200°F -18 TO 93°C	-0 TO 200°F -18 TO 93°C	-0 TO 250°F -18 TO 121°C	-0 TO 250°F -18 TO 212°C	-67 TO 500°F -55 TO 260°C	-100 - 200°F -73C - 90°C
BREATHABLE OR DUST-TIGHT CFM AIRFLOW AT 0.5" WG	NEARLY DUST-TIGHT 0.5 CFM	BREATHABLE 30 CFM	DUST-TIGHT 0 CFM	BREATHABLE 5-15 CFM	BREATHABLE 20-35 CFM	BREATHABLE 20-30 CFM	BREATHABLE 8.5 CFM	DUST-TIGHT 0 CFM	NEARLY DUST-TIGHT 0.5CFM
FDA FOR DIRECT FOOD CONTACT	YES	YES	YES	YES	YES	YES	YES	NO	YES
EC FOOD SAFETY COMPLIANT	YES	YES	YES	YES	YES	YES	YES	NO	NO
STATIC CONTROL OPTIONS	ADD GROUND WIRE	ADD GROUND WIRE	ADD GROUND WIRE	ADD GROUND WIRE	ADD GROUND WIRE	ADD GROUND WIRE	WOVEN-IN GROUND WIRE	ADD GROUND WIRE	ADD GROUND WIRE

★ OUTSTANDING
★★★★★ EXCELLENT
★★★★★ VERY GOOD
★★★★★ GOOD
★★★★★ FAIR
★★★★★ POOR

OFFICE 52D CONNECTICUT AVENUE
SOUTH WINDSOR, CONNECTICUT 06074
WEBSITE WWW.SIFTEX.COM

EMAIL CUSTOMERSERVICE@SIFTEX.COM
PHONE 800-274-3839 / 860-289-8779
FAX 860-289-8744

Siftex is focused on helping you spend less time with downtime by providing the innovative products, personal attention, superior customer service and on-time deliveries you expect.

